Mini Florence

This is the same as the Florence fitting but sufficiently smaller so that it can be used in standard corridors which typically have a width of 1.5M. This is small enough not to make the ceiling appear crowded and can even be wall mounted. The effect is the upmarket hotel feel to the navigational walkways of a building. The choice of bezel finish can add dramatic effects. The main benefit is you create that effect with the same energy and maintenance savings as say the Monza range.



Key Points

Accepts any of the Lux Bright technologies on a fully removable steel gear tray. Highly functional therefore typical generates significant long term reduced energy and maintenance costs. Ideal for corridors, stairwells and entrance areas where you want to create a visually stimulating environment. Aesthetically pleasing. High reliability. 20W LED and 22W fluorescent versions.

Excellent colour rendering CRI >0.85. Full 5 year warranty.

Construction

Spun steel body and bezel powder coated in gloss white. Different finishes including Satin Nickel, Antique Brass and Polished Chrome are available.


UV, fire retardant and high impact polycarbonate clear or opal prismatic diffuser.

Specification

The Lux Bright microwave sensor can be customised to the needs of an individual site. Integral emergency battery backup options, emergency lighting guard options and the ability to run off of central battery systems. The later 2 options are site specific. RF control between fittings is available. Fused terminal blocks*

Installation

Can be ceiling or wall mounted. Cable entry to the rear of the fitting, mini trunking may be used but will damage aesthetic impact. 4 pole male and female connector block as standard.



······································						
Name of Fitting	Light Source	Wattage	Lighting Technology	Colour of Body	Emergency Options	Diffuser Colour
Mini Flor- ence	LED FLU	20W 22W	Dim10% DimOnOff Switched RF	WH (White) PC (Polished Chrome) AB (Antique Brass)	EM3 Self Test	Clear (CL) Opal (OP)

lame Of Fitting / Light Source / Wattage / Lighting Technology / Colour of Body / Emergency Options / Diffuser Colour

Stock Code

emplate for Determining Part Codes:-

MiniFlorence/LED/20W/Dim10%/WH/CL MiniFlorence/LED/20W/Dim10%/WH/EM3/CL MiniFlorence/LED/20W/DimOnOff/WH/CL MiniFlorence/LED/20W/DimOnOff/WH/EM3/CL MiniFlorence/LED/20W/Switched/WH/CM3/CL Description 20W LED FTG Dims to 10%, WH Body, CL Diff EMG 20W LED FTG Dims to 10%, WH Body, CL Diff 20W LED FTG Sensor On or Off, WH Body, CL Diff 20W LED Switched, WH body, CL Diff 20W LED Switched, WH body, CL Diff